

Declaration of Performance – Ref.No 015

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	High-pressure decorative compact laminate CGS-LK														
2. Identification	CGS-LK: Duropal HPL Compact, black core / Duropal HPL Compact Individual Motiv, black core														
3. Intended use	Compact laminate intended for internal wall and ceiling finishes (including suspended ceilings)														
4. Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D – 88299 Leutkirch														
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt														
6. System of assessment and verification	System 4														
7. Assessment of performance	not relevant														
8. European Technical Assessment	not relevant														
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>CGS-LK</th> <th>CGS-LK</th> <th>CGS-LK</th> <th>CGS-LK</th> </tr> </thead> <tbody> <tr> <td>Thickness</td> <td>4–5 mm</td> <td>6 mm</td> <td>8 mm</td> <td>10–15 mm</td> </tr> </tbody> </table>				Identification code	CGS-LK	CGS-LK	CGS-LK	CGS-LK	Thickness	4–5 mm	6 mm	8 mm	10–15 mm	<i>Harmonised technical specification</i> EN 438-7:2005
Identification code	CGS-LK	CGS-LK	CGS-LK	CGS-LK											
Thickness	4–5 mm	6 mm	8 mm	10–15 mm											
<i>Essential characteristics/main features</i>	<i>Declared performance</i>														
Reaction to fire (Euroclass)	NPD	D-s2,d0													
Fire resistance	NPD														
Water vapour permeability (wet cup)	110														
Water vapour permeability (dry cup)	250														
Resistance to fixings (face)	min. 1,000 N	min. 2,000 N	min. 3,000 N	min. 4,000 N											
Resistance to fixings (edge)	NPD														
Direct airborne sound insulation	NPD														
Flexural strength	min. 80 MPa														
Bending modulus of elasticity	min. 9,000 MPa														
Thermal conductivity	approx. 0.3 W/(mK)														
Formaldehyde release	E1														
Sound absorption	NPD														
Durability – Resistance to immersion in boiling water	passed														
Density	min. 1,350 kg/m ³														
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.															

Signed for and on behalf of the manufacturer by:

Date of issue: 2022-12-02

Diethard Singer
 General Manager / Pfleiderer Leutkirch GmbH
 (Document was created electronically and is therefore valid without signature!)

NPD: performance not defined