

Declaration of Performance – Ref.No 031

acc. to REGULATION (EU) No 305/2011 Article 4

1. Identification code of product-type	Lacquered, decorative particleboard PB180-LK																																																																				
2. Identification	PB180-LK: PrimeBoard XTreme P3																																																																				
3. Intended use	Non load-bearing boards for use in humid conditions																																																																				
4. Manufacturer	Pfleiderer Leutkirch GmbH, Wurzacher Str. 32, D – 88299 Leutkirch																																																																				
5. Authorised representative	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt																																																																				
6. System of assessment and verification	System 4																																																																				
7. Assessment of performance	not relevant																																																																				
8. European Technical Assessment	not relevant																																																																				
9. Declared performance	<table border="1"> <thead> <tr> <th>Identification code</th> <th>PB180-LK</th> <th>PB180-LK</th> <th>PB180-LK</th> <th rowspan="2">Harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td>Thickness</td> <td>13–19 mm</td> <td>22–25 mm</td> <td>28 mm</td> <td rowspan="15">EN 13986:2004 +A1:2015</td> </tr> <tr> <td><i>Essential characteristics/main features</i></td> <td colspan="3"><i>Declared performance</i></td> </tr> <tr> <td>Reaction to fire (Euroclass)</td> <td colspan="3">D-s2,d0 according to EN 13986 dependent on end use (Thickness: ≥ 9 mm / Gross density: ≥ 600 kg/m³)</td> </tr> <tr> <td>Water vapour permeability (wet cup)</td> <td colspan="3">15</td> </tr> <tr> <td>Water vapour permeability (dry cup)</td> <td colspan="3">50</td> </tr> <tr> <td>Formaldehyde release</td> <td colspan="3">E1 E05</td> </tr> <tr> <td>content of pentachlorophenol</td> <td colspan="3">≤ 3 ppm</td> </tr> <tr> <td>Airborne sound insulation (surface mass)</td> <td colspan="3">NPD</td> </tr> <tr> <td>Sound Absorption frequency range 250 Hz to 500 Hz</td> <td colspan="3">0.1</td> </tr> <tr> <td>Sound Absorption frequency range 1000 Hz to 2000 Hz</td> <td colspan="3">0.25</td> </tr> <tr> <td>Thermal conductivity</td> <td colspan="3">NPD</td> </tr> <tr> <td>Air permeability</td> <td colspan="3">NPD</td> </tr> <tr> <td>Internal bond</td> <td>0.45 N/mm²</td> <td>0.4 N/mm²</td> <td>0.35 N/mm²</td> </tr> <tr> <td>Swelling in thickness, 24 h</td> <td colspan="3">NPD</td> </tr> <tr> <td>Internal bond after boil test</td> <td colspan="3">NPD</td> </tr> </tbody> </table>			Identification code	PB180-LK	PB180-LK	PB180-LK	Harmonised technical specification	Thickness	13–19 mm	22–25 mm	28 mm	EN 13986:2004 +A1:2015	<i>Essential characteristics/main features</i>	<i>Declared performance</i>			Reaction to fire (Euroclass)	D-s2,d0 according to EN 13986 dependent on end use (Thickness: ≥ 9 mm / Gross density: ≥ 600 kg/m ³)			Water vapour permeability (wet cup)	15			Water vapour permeability (dry cup)	50			Formaldehyde release	E1 E05			content of pentachlorophenol	≤ 3 ppm			Airborne sound insulation (surface mass)	NPD			Sound Absorption frequency range 250 Hz to 500 Hz	0.1			Sound Absorption frequency range 1000 Hz to 2000 Hz	0.25			Thermal conductivity	NPD			Air permeability	NPD			Internal bond	0.45 N/mm ²	0.4 N/mm ²	0.35 N/mm ²	Swelling in thickness, 24 h	NPD			Internal bond after boil test	NPD		
Identification code	PB180-LK	PB180-LK	PB180-LK	Harmonised technical specification																																																																	
Thickness	13–19 mm	22–25 mm	28 mm		EN 13986:2004 +A1:2015																																																																
<i>Essential characteristics/main features</i>	<i>Declared performance</i>																																																																				
Reaction to fire (Euroclass)	D-s2,d0 according to EN 13986 dependent on end use (Thickness: ≥ 9 mm / Gross density: ≥ 600 kg/m ³)																																																																				
Water vapour permeability (wet cup)	15																																																																				
Water vapour permeability (dry cup)	50																																																																				
Formaldehyde release	E1 E05																																																																				
content of pentachlorophenol	≤ 3 ppm																																																																				
Airborne sound insulation (surface mass)	NPD																																																																				
Sound Absorption frequency range 250 Hz to 500 Hz	0.1																																																																				
Sound Absorption frequency range 1000 Hz to 2000 Hz	0.25																																																																				
Thermal conductivity	NPD																																																																				
Air permeability	NPD																																																																				
Internal bond	0.45 N/mm ²	0.4 N/mm ²	0.35 N/mm ²																																																																		
Swelling in thickness, 24 h	NPD																																																																				
Internal bond after boil test	NPD																																																																				
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.																																																																					

Signed for and on behalf of the manufacturer by:

Date of issue: 2023-07-25

Diethard Singer
General Manager / Pfleiderer Leutkirch GmbH
(Document was created electronically and is therefore valid without signature!)

NPD: performance not defined
Technical values refer to the core material